

ReweightOOD: Loss Reweighting for Distance-based OOD Detection

Supplementary Material

7.1. Pseudocode of ReweightOOD

The general working algorithm of ReweightOOD framework is given in Algorithm 1. Moreover, the loss formulation optimizes maximizing the cosine similarity between positive pairs and minimizing the cosine similarity between negative pairs. The loss is weighted by the weighting mechanism as shown in the algorithm.

7.2. Ablation on linear transformation

To investigate the effect of linear transformation prior to sigmoid weighting, we compare the use of linear transformation with the use of the original cosine similarity range for both within-class and between-class similarity. The results in Table 9 (FPR metric) and Table 10 (AUROC metric) show that the use of linear transformation as opposed to just using original cosine similarity enhances the performance of OOD detection.

7.3. Stability of ReweightOOD

We perform 3 independent trials using ResNet18 network to verify strong performance of ReweightOOD in comparison to baseline with CIFAR100 datasets. The OOD detection performance metrics in FPR metrics in the form of $\text{mean}_{\pm\text{std}}$ presented in Table 11 verifies effectiveness of our approach.

7.4. Additional CIFAR100 results

The OOD detection performance in various OOD datasets obtained with DenseNet architecture trained with the CIFAR-100 dataset in terms of FPR metric is summarized in Table 12. The superior performance of ReweightOOD is evident from the presented results.

7.5. CIFAR10 results

For CIFAR10 (ID) experiments, the comparison of our method with various non-contrastive as well as contrastive approaches is presented in Table 13. In the non-contrastive approach, We compare our approach with posthoc methods such as MSP [15], ODIN [25], Mahalanobis [23], DICE [40] and Energy [27] as well as training-time regularization approaches such as GODIN [17] and Logit-Norm [50]. In contrastive approaches, we compare with ProxyAnchor [20], CSI [43], SSD+ [37], KNN+ [42], and CIDER [31]. In contrastive approaches, we compare our method with ProxyAnchor [20], CSI [43], SSD+ [37], KNN+ [42], and CIDER [31]. We use default hyperparameters provided in the original work whenever required. Our approach leads to the best performance in both metrics. We can observe that the majority of the methods work well

since it is a relatively easier task because of the smaller number of classes in comparison to CIFAR100. However, our approach still outperforms the current approaches on average FPR and AUROC metrics.

7.6. Compatibility with Mahalanobis distance CIFAR experiments.

The OOD detection score using Mahalanobis distance using CIFAR-10 experiments is shown in Table 14 and Table 15. Also, the OOD detection performance using CIFAR-100 experiments in terms of the AUROC metric is also shown in Table 16. Experiments are performed using the ResNet-18 network. The results presented show that our approach consistently remains superior in OOD detection performance.

7.7. OOD detection performance in ImageNet dataset in terms of AUROC metrics.

Further OOD detection performance in ImageNet100 experiments in terms of AUROC is presented in Table 17. Fine-tuning pretrained ResNet50 model with our approach leads to the superior AUROC metric in comparison to baseline and SupCon loss formulations. This shows the potential of ReweightOOD to be used in the fine-tuning context too.

7.8. Implementation platform

All the experiments were performed on NVIDIA A100 GPU with PyTorch deep learning library (version: 1.8).

7.9. Datasets

7.9.1 ID datasets

CIFAR-10, CIFAR-100 and ImageNet-100 are three ID datasets used in our experiments.

CIFAR CIFAR-10 is one of the most commonly used datasets for benchmarking computer vision performance, especially for classification tasks. It contains 10 categories of images. There are 50,000 training and 10,000 testing samples totalling 60,000 samples. CIFAR-100 is a very similar dataset to CIFAR-10 but consists of 100 classes. It contains the same number of images as CIFAR-10, however number of images per category is smaller. The CIFAR images exhibit a square resolution with a width of 32 pixels.

ImageNet100 ImageNet-100 dataset is a subset of ImageNet dataset. ImageNet-100 consists of images from 100 randomly sampled categories from the original ImageNet dataset. The images of the ImageNet100 dataset are trained in the square resolution with a width of 224 pixels.

Algorithm 1: Training Loop for the ReweightOOD framework

Data: Training data: X, Y (labels)
Result: Trained model parameters: f_θ

- 1 Initialize model parameters f_θ and projection head g_θ ;
- 2 Define learning rate α ;
- 3 Define linear transformation constant m_w, c_w, m_b, c_b ;
- 4 Define the number of epochs N ;
- 5 **for** $epoch \leftarrow 1$ **to** N **do**
- 6 **for** $each (x_i, y_i)$ **in** X, Y **do**
- 7 Apply random augmentations $x_i = RandomAugment(x_i)$;
- 8 Compute encoded representation $h_i = f_\theta(g_\theta(x_i))$;
- 9 Transform to hyperspherical embeddings $\hat{h}_i = L2_Normalize(h_i)$;
- 10 similarity_matrix = embeddings @ embeddings.transpose(1, 0) ;
- 11 label_matrix = label.unsqueeze(1) == label.unsqueeze(0) ;
- 12 within_class_matrix = label_matrix.triu(diagonal=1) ;
- 13 between_class_matrix = label_matrix.logical_not().triu(diagonal=1);
- 14 similarity_matrix = similarity_matrix.view(-1) ;
- 15 within_class_matrix = within_class_matrix.view(-1);
- 16 between_class_matrix = between_class_matrix.view(-1);
- 17 $s_w^j = similarity_matrix[within_class_matrix]$;
- 18 $s_b^i = similarity_matrix[between_class_matrix]$;
- 19 $w_w^j = sigmoid(m_w \cdot s_w + c_w)$;
- 20 $w_b^i = sigmoid(m_b \cdot s_b + c_b)$;
- 21 loss = $\log(\sum_{i=1}^n \exp(w_b^i \cdot s_b^i / \tau)) - \log(\sum_{j=1}^m \exp(w_w^j \cdot s_w^j / \tau))$;
- 22 Compute gradients with respect to model parameters ;
- 23 Update learnable parameters: $\theta \leftarrow \theta - \alpha \nabla L_i$;
- 24 **return** Trained model parameters f_θ ;

Table 9. Ablation on use of linear transformation in the weighting of (s_w, s_b) and OOD detection performance in terms of FPR metric.

Method	OOD Dataset							
	MNIST	iSUN	LSUN	LSUN-r	SVHN	Texture	Places365	Average
Without linear transformation (Original range)	64.47	77.14	34.46	75.42	17.54	33.40	80.72	54.74
Without linear transformation in s_w weighting	68.79	56.80	22.18	56.49	12.61	37.82	78.79	47.64
Without linear transformation in s_b weighting	48.67	74.53	39.23	70.48	14.83	31.86	77.65	51.04
(ReweightOOD) Ours	19.24	57.56	19.59	56.31	8.39	28.72	78.70	38.36

Table 10. Ablation on use of linear transformation in weighting of (s_w, s_b) and OOD detection performance in terms of AUROC metric.

Method	OOD Dataset							
	MNIST	iSUN	LSUN	LSUN-r	SVHN	Texture	Places365	Average
Without linear transformation (Original range)	84.16	81.75	90.47	83.01	96.16	92.47	75.85	86.27
Without linear transformation in s_w weighting	87.98	88.35	95.67	88.92	97.72	92.62	76.52	89.68
Without linear transformation in s_b weighting	89.00	82.85	90.47	84.26	96.95	92.85	77.94	87.76
(ReweightOOD) Ours	96.86	87.54	96.86	88.23	98.31	94.11	76.01	90.91

7.9.2 OOD datasets

We use the following OOD datasets: MNIST, iSUN, LSUN-R, LSUN-C, Places365, SVHN, Texture, iNaturalists, NINCO, OpenImage, and Semantic Shift Benchmark

(SSB).

MNIST MNIST dataset consists of 70,000 grayscale images. Each image represents a handwritten digit ranging from 0 to 9 in a resolution of 28x28 pixels. MNIST dataset consists of 60,000 training 10,000 testing images.

Table 11. OOD detection performance across 3 independent trials using ResNet18 trained with CIFAR100 datasets in FPR metric.

ID dataset	OOD Dataset							Average
	MNIST	iSUN	LSUN	LSUN-r	SVHN	Texture	Places365	
Baseline	72.58 \pm 7.01	74.95 \pm 14.62	46.05 \pm 7.58	72.00 \pm 13.79	25.08 \pm 1.70	42.33 \pm 3.08	71.56 \pm 2.18	57.79 \pm 5.53
(ReweightOOD) Ours	16.84 \pm 5.99	68.05 \pm 8.10	24.06 \pm 9.71	67.21 \pm 8.11	9.01 \pm 2.03	27.36 \pm 2.76	79.59 \pm 2.08	41.73\pm2.56

Table 12. OOD detection performance using CIFAR-100(ID) with DenseNet architecture in terms of FPR.

Method	OOD Dataset							Average FPR ↓
	MNIST	iSUN	LSUN	LSUN-r	SVHN	Texture	Places365	
Baseline	37.32	39.66	35.63	46.58	11.15	20.43	82.45	39.03
SupCon	26.97	61.00	30.60	70.02	9.93	22.13	89.34	44.28
(ReweightOOD) Ours	10.39	24.45	36.86	29.96	14.26	18.53	85.08	31.36

Table 13. Mean OOD detection performance for CIFAR-10 (ID) with ResNet-18.

Method	MNIST		iSUN		LSUN		OOD Dataset LSUN-r		SVHN		Texture		Places365		Average	
	FPR↓	AUROC↑	FPR↓	AUROC↑	FPR↓	AUROC↑	FPR↓	AUROC↑	FPR↓	AUROC↑	FPR↓	AUROC↑	FPR↓	AUROC↑	FPR↓	AUROC↑
	Without Contrastive Learning															
MSP	45.93	93.02	47.42	92.07	30.90	95.49	45.77	92.78	46.76	92.33	52.82	90.44	55.05	89.03	46.38	92.17
ODIN	20.45	95.37	24.96	93.32	16.33	95.93	22.64	94.31	51.00	84.36	41.93	87.35	50.17	84.35	32.50	90.71
Mahalanobis	77.84	88.43	30.44	94.67	79.41	86.19	30.54	94.80	64.60	90.21	36.05	93.29	58.53	88.42	53.92	90.86
Energy	23.77	95.20	36.45	91.65	13.04	97.36	33.91	92.78	33.16	92.49	41.77	90.26	42.63	89.15	32.11	92.70
DICE	12.57	97.63	73.46	80.54	12.37	97.29	72.14	81.75	30.48	93.93	58.81	82.55	64.32	78.87	46.31	87.51
GODIN	5.53	98.77	12.48	97.55	6.55	98.64	10.73	97.88	14.39	97.62	20.59	96.05	40.89	90.24	15.88	96.68
LogitNorm	3.16	99.16	23.87	96.23	0.47	99.83	20.84	96.72	13.71	97.63	27.94	95.10	30.29	94.92	17.18	97.08
With Contrastive Learning																
ProxyAnchor	7.77	98.72	26.13	96.09	4.26	98.99	21.36	96.54	1.04	99.80	9.68	98.44	19.20	96.51	12.78	97.87
CSI	4.20	98.32	45.36	92.33	20.62	97.07	47.07	92.16	4.58	99.02	14.66	97.66	58.67	88.71	27.88	95.04
SSD+	2.74	99.34	54.62	93.16	5.04	99.05	52.17	93.55	0.45	99.90	9.08	98.49	24.15	96.22	21.18	97.10
KNN+	4.95	99.09	21.23	96.53	4.52	99.16	21.83	96.44	1.74	99.64	8.88	98.48	21.28	96.43	12.06	97.97
CIDER	31.03	94.97	13.67	97.36	4.07	99.26	14.40	97.31	2.85	99.54	18.55	97.15	30.27	95.17	16.41	97.25
Baseline	10.25	98.37	18.12	96.99	8.51	98.59	17.20	97.14	1.43	99.75	9.11	98.51	24.04	96.07	12.67	97.92
(ReweightOOD) Ours	10.99	97.92	10.85	98.00	3.42	99.23	10.99	97.94	1.03	99.82	9.75	98.47	22.72	95.97	9.96	98.19

Table 14. Compatibility with MDS using CIFAR-10 (ID) in terms of FPR metric.

Method	iSUN	LSUN	LSUN-r	SVHN	Texture	Places365	Average FPR
ProxyAnchor	55.83	4.42	51.43	0.14	13.37	24.60	24.96
SSD+	46.60	2.56	42.16	0.28	8.67	22.23	20.42
CIDER	53.32	17.17	51.27	0.86	22.30	45.06	31.66
(ReweightOOD) Ours	30.67	6.26	26.91	0.10	8.59	22.64	15.86

Table 15. Compatibility with MDS using CIFAR-10 (ID) in terms of AUROC metric.

Method	iSUN	LSUN	LSUN-r	SVHN	Texture	Places365	Average FPR
ProxyAnchor	92.48	99.10	93.19	99.95	97.92	96.08	96.45
SSD+	93.90	99.36	94.46	99.93	98.56	96.36	97.10
CIDER	93.74	97.77	93.86	99.80	96.56	93.70	95.91
(ReweightOOD) Ours	95.65	98.80	96.07	99.96	98.50	96.31	97.55

SVHN SVHN is a real-world digit recognition dataset obtained from house numbers in Google Street View images. It is similar to MNIST images but the difficulty of recognition for machine learning algorithms is a more harder.

LSUN LSUN datasets are curated for the purpose of scene understanding. It has three variations.

Places365 Places365 is also another large-scale scene dataset developed for training deep-learning models to un-

Table 16. Compatibility with MDS using CIFAR-100 (ID) in terms of AUROC metric.

Method	MNIST	iSUN	LSUN	LSUN-r	SVHN	Texture	Places365	Average AUROC \uparrow
ProxyAnchor	76.32	75.41	90.23	75.81	98.47	87.08	82.66	83.71
SSD+	76.80	83.85	89.91	85.19	95.70	88.22	80.86	85.79
CIDER	75.78	79.17	95.98	79.38	97.99	90.10	80.30	85.53
(ReweightOOD) Ours	87.59	86.30	96.68	86.79	98.81	91.01	81.70	89.84

Table 17. OOD detection performance in large-scale experiments (ImageNet-100) in terms of AUROC by fine-tuning pretrained ResNet50.

Method	iNaturalist	SUN	Textures	Places	SSB Hard	Ninco	Openimage	Average AUROC \downarrow
Baseline	99.15	99.35	99.12	98.56	92.17	94.46	98.47	97.32
SupCon	99.15	99.35	99.12	98.56	92.17	95.46	98.47	97.32
(ReweightOOD) Ours	99.36	99.26	99.45	98.49	92.29	95.16	98.81	97.55

derstand scenes.

Texture The Textures dataset contains images of various textures which are unique images apart from widely available object or scene images.

iNaturalist iNaturalist contains images of the natural world. It has 13 super-categories and 5,089 sub-categories covering various aspects of natural realms such as plants, insects, birds, mammals, etc.

NINCO The NINCO (No ImageNet Class Objects) dataset comprises 64 OOD classes, encompassing a total of 5879 samples. These OOD classes were thoughtfully chosen to ensure the complete absence of categorical overlap with any of the 1000 classes found in ImageNet-1K. Subsequently, a rigorous individual inspection of each sample was conducted to verify the absence of any objects from the ID categories.

SSB SSB is a dataset for open-set recognition, category discovery, out-of-distribution detection, etc. The SSB is intended to isolate semantic novelty from other forms of distributional shifts. It contains easy and hard split, but we make use of hard split.

OpenImage-O OpenImage-O is curated by selecting images on an individual basis from the test set of OpenImage-V3, which, in turn, was taken from the vast repository of Flickr without the imposition of a predetermined list of class names or tags. This dataset is manually annotated and has a diverse distribution.

In all OOD datasets, samples duplicating in ID datasets are removed wherever needed hence obtaining subset the subset different from ID.