

# Restora-Flow: Mask-Guided Image Restoration with Flow Matching (Supplemental Material)

Arnela Hadzic<sup>1</sup>, Franz Thaler<sup>1,2,3</sup>, Lea Bogensperger<sup>4</sup>, Simon Johannes Joham<sup>1</sup>, Martin Urschler<sup>1</sup>


<sup>1</sup>Institute for Medical Informatics, Statistics and Documentation, Medical University of Graz, Graz, Austria

<sup>2</sup>Division of Medical Physics and Biophysics, Medical University of Graz, Graz, Austria


<sup>3</sup>Institute of Visual Computing, Graz University of Technology, Graz, Austria

<sup>4</sup>Department of Quantitative Biomedicine, University of Zurich, Zurich, Switzerland


{arnela.hadzic, martin.urschler}@medunigraz.at




Supplemental Figure 1. Qualitative results on COCO. Shown are the degraded image (col 1), original image (col 2), restored images using related work as indicated (cols 3-8) and restored images of Restora-Flow (col 9). Rows refer to denoising (row 1), box inpainting (row 2), super-resolution (row 3) and random inpainting (row 4). Differences can be best seen in the pdf version.




Supplemental Figure 2. Visual representation of quantitative results on CelebA. Restora-Flow ( $\diamond$ ) is compared to related work methods (other shapes) on four different tasks (colors). The plots represent LPIPS  $\downarrow$  (left), SSIM  $\uparrow$  (center) and PSNR  $\uparrow$  (right) on the y-axis, and processing time  $\downarrow$  (all plots) on the x-axis. For better visualization and comparison, each plot is separated into two parts with different scales in the x-axis.



Supplemental Figure 3. Qualitative results on X-ray Hand. Shown are the degraded image (col 1), original image (col 2), restored images using related work as indicated (cols 3-8) and restored images of Restora-Flow (col 9). Rows refer to different tasks as indicated. RePaint is not applicable to denoising (N/A).



Supplemental Figure 4. Qualitative comparison of image restoration methods on CelebA using various input masks. Differences can be best seen in the pdf version.



Supplemental Figure 5. Representative failure cases of Restora-Flow and comparison methods. (a) A face in profile view, deviating from the typically front-facing images in CelebA. (b) An example with occlusion due to glasses (CelebA). (c) An atypical AFHQ-Cat image where the cat's appearance differs from typical samples in the dataset (*e.g.*, ears not visible).